

Comparing speed of packages for computing ROC curves

Toby Dylan Hocking

July 11, 2017

1 Introduction

The goal of this vignette is to compare how long it takes to compute the ROC curves and AUC using different R packages: WeightedROC, ROCR, pROC, glmnet.

2 Data

The data set I will analyze is the `spam` data set discussed in the book “The Elements of Statistical Learning” by Hastie, Tibshirani, and Friedman. The book is available to read for free as a downloadable PDF at

<http://statweb.stanford.edu/~tibs/ElemStatLearn/>

The data set is available in the R package `ElemStatLearn`:

```
> library(ElemStatLearn)
> data(spam)
> is.label <- names(spam) == "spam"
> X <- as.matrix(spam[,!is.label])
> y <- spam[,is.label]
> set.seed(1)
> train.i <- sample(nrow(spam), nrow(spam)/2)
> sets <-
+   list(train=list(features=X[train.i, ], label=y[train.i]),
+         test=list(features=X[-train.i, ], label=y[-train.i]))
> str(sets)
```

List of 2

```
$ train:List of 2
..$ features: num [1:2300, 1:57] 0 0 0 0 0 0 0 0 0 0.4 ...
.. ..- attr(*, "dimnames")=List of 2
.. .. ..$ : chr [1:2300] "1222" "1712" "2635" "4176" ...
.. .. ..$ : chr [1:57] "A.1" "A.2" "A.3" "A.4" ...
..$ label : Factor w/ 2 levels "email","spam": 2 2 1 1 2 1 1 1 1 2 ...
$ test :List of 2
..$ features: num [1:2301, 1:57] 0 0 0.06 0 0 0 0 0 0 0.05 ...
.. ..- attr(*, "dimnames")=List of 2
.. .. ..$ : chr [1:2301] "1" "7" "10" "12" ...
.. .. ..$ : chr [1:57] "A.1" "A.2" "A.3" "A.4" ...
..$ label : Factor w/ 2 levels "email","spam": 2 2 2 2 2 2 2 2 2 2 ...
```

I divided the data set into half train, half test. I will fit a model on the training set and see if it works on the test set.

3 Model fitting

Below, I fit an L1-regularized logistic regression model to the spam training set.

```

> library(glmnet)
> system.time({
+   fit <- cv.glmnet(sets$train$features, sets$train$label, family="binomial")
+ })

      user  system elapsed
16.572    0.012   16.640

```

On my Intel i7 2.8GHz CPU, it took about 10 seconds to fit the model.

4 Timing test ROC curve computation

ROC analysis is useful for evaluating binary classifiers. Below we compute the ROC curves using WeightedROC, pROC, and ROCR.

```

> library(WeightedROC)
> library(ROCR)
> library(pROC)
> set <- sets$test
> guess <- predict(fit, set$features)
> if(require(microbenchmark)){
+   microbenchmark(WeightedROC={
+     wroc <- WeightedROC(guess, set$label)
+   }, ROCR={
+     pred <- prediction(guess, set$label)
+     perf <- performance(pred, "tpr", "fpr")
+   }, pROC={
+     proc <- roc(set$label, guess, algorithm=2)
+   })
+ }

```

Unit: milliseconds

	expr	min	lq	mean	median	uq	max	neval
WeightedROC		3.214201	3.430741	4.563544	3.924361	5.35343	13.49265	100
ROCR		6.835659	7.247196	9.522626	10.115177	11.20842	16.45128	100
pROC		27.939451	28.895652	39.996864	41.944814	49.70992	55.11324	100

cld
a
b
c

It is clear that WeightedROC is the fastest computation (on my computer, median 1.8 milliseconds), followed by ROCR (7.2 milliseconds), and finally pROC (26.4 milliseconds). However, all of the ROC computations are much faster than the model fitting (10 seconds). Below, we plot the ROC curves.

```


> perfDF <- function(p){
+   data.frame(FPR=p@x.values[[1]], TPR=p@y.values[[1]], package="ROCR")
+ }
> procDF <- function(p){
+   data.frame(FPR=1-p$specificities, TPR=p$sensitivities, package="pROC")
+ }
> roc.curves <-
+   rbind(data.frame(wroc[,c("FPR", "TPR")], package="WeightedROC"),
+         perfDF(perf), procDF(proc))
> library(ggplot2)
> rocPlot <- ggplot()+
+   geom_path(aes(FPR, TPR, color=package, linetype=package),

```

```

+       data=roc.curves, size=1)+
+   coord_equal()
> print(rocPlot)
>

```



5 Scaling

In this section I was interested in seeing if there are any differences between algorithms as the number of data points changes.

```


> if(require(microbenchmark)){
+   stats.by.size.expr <- list()
+   ms.by.size <- list()
+   for(size in c(400, 800, 1200, 1500, 2000, 2300)){
+     indices <- seq(1, length(set$label), l=size)
+     y <- set$label[indices]
+     y.hat <- guess[indices]
+     this.size <- microbenchmark(WeightedROC={
+       wroc <- WeightedROC(y.hat, y)
+     }, ROCR={

```

```

+     pred <- prediction(y.hat, y)
+     perf <- performance(pred, "tpr", "fpr")
+   }, pROC.1={
+     proc <- roc(y, y.hat, algorithm=1)
+   }, pROC.2={
+     proc <- roc(y, y.hat, algorithm=2)
+   })
+   this.size$milliseconds <- this.size$time/1e6
+   ms.by.size[[paste(size)]] <- data.frame(size, this.size)
+   this.by.expr <- split(this.size, this.size$expr)
+   for(expr in names(this.by.expr)){
+     stats <- with(this.by.expr[[expr]], {
+       data.frame(median=median(milliseconds),
+                 q25=quantile(milliseconds, 0.25),
+                 q75=quantile(milliseconds, 0.75))
+     })
+     stats.by.size.expr[[paste(size, expr)]] <- data.frame(size, expr, stats)
+   }
+ }
+ ms <- do.call(rbind, ms.by.size)
+ algo.stats <- do.call(rbind, stats.by.size.expr)
+ timePlot <- ggplot()+
+   geom_ribbon(aes(size, ymin=q25, ymax=q75, fill=expr),
+             data=algo.stats, alpha=1/2)+
+   geom_line(aes(size, median, color=expr), data=algo.stats, size=2)+
+   geom_point(aes(size, milliseconds, color=expr), data=ms, pch=1)+
+   ylab("milliseconds")+
+   xlab("data set size")+
+   ggtitle("mean +/- 1 standard deviation")
+ print(timePlot)
+ }

```



The figure above shows that for the spam data, the data set size does not affect the speed ordering of the algorithms for ROC curve computation. In all cases, WeightedROC is fastest, followed by ROCR, then pROC.2, then pROC.1. It makes sense that pROC.2 is faster than pROC.1, since pROC.2 uses the cumsum function, but pROC.1 does not.