

# Package ‘fixes’

April 23, 2025

**Type** Package

**Title** Tools for Creating and Visualizing Fixed-Effects Event Study Models

**Version** 0.2.0

**Description**

Provides functions for creating, analyzing, and visualizing event study models using fixed-effects regression.

**Depends** R (>= 4.1.0)

**Imports** dplyr, ggplot2, fixest, broom, tibble, rlang

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Suggests** knitr, rmarkdown

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Yosuke Abe [aut, cre]

**Maintainer** Yosuke Abe <yosuke.abe0507@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-04-23 14:20:02 UTC

## Contents

plot_es . . . . .	2
run_es . . . . .	4
<b>Index</b>	<b>8</b>

## Description

This function creates a plot for event study results using 'ggplot2'. Users can choose between ribbon-style confidence intervals or error bars to visualize the estimates and their uncertainty.

## Usage

```
plot_es(
  data,
  type = "ribbon",
  vline_val = 0,
  vline_color = "#000",
  hline_val = 0,
  hline_color = "#000",
  linewidth = 1,
  pointsize = 2,
  alpha = 0.2,
  barwidth = 0.2,
  color = "#B25D91FF",
  fill = "#B25D91FF"
)
```

## Arguments

data	A dataframe containing the results from the 'run_es' function. The dataframe must include the following columns: - 'relative_time': The scaled time relative to the treatment. - 'estimate': The estimated coefficients. - 'conf_low': The lower bound of the 95 - 'conf_high': The upper bound of the 95 - 'std.error': The standard errors (required if 'type = "errorbar"').
type	The type of confidence interval visualization: "ribbon" (default) or "errorbar". - "ribbon": Shaded area representing the confidence intervals. - "errorbar": Vertical error bars for each estimate.
vline_val	The x-intercept for the vertical reference line (default: 0). Typically represents the time of treatment.
vline_color	The color of the vertical reference line (default: "#000").
hline_val	The y-intercept for the horizontal reference line (default: 0). Usually represents the null effect line.
hline_color	The color of the horizontal reference line (default: "#000").
linewidth	The width of the lines in the plot (default: 1).
pointsize	The size of the points for the estimates (default: 2).
alpha	The transparency level for the ribbon (default: 0.2).

barwidth	The width of the error bars (default: 0.2).
color	The color of the lines and points (default: "#B25D91FF").
fill	The fill color for the ribbon (default: "#B25D91FF").

### Details

This function provides a flexible visualization tool for event study results. Users can customize the appearance of the plot by adjusting the parameters for line styles, point sizes, colors, and confidence interval types.

**\*\*Column Requirements\*\*:** The input dataframe ('data') must include: - 'relative\_time': A numeric column for the time relative to the treatment. - 'estimate': The estimated coefficients for each relative time. - 'conf\_low' and 'conf\_high': The bounds of the confidence intervals. - 'std.error': The standard errors (only required if 'type = "errorbar"').

**\*\*Type Options\*\*:** - "ribbon": A shaded area to represent the confidence intervals. - "errorbar": Error bars for each point. Standard errors ('std.error') are required.

### Value

A ggplot object displaying the event study results. The plot includes: - A line connecting the estimates over relative time. - Points for the estimated coefficients. - Either ribbon-style confidence intervals or error bars, depending on 'type'. - Vertical and horizontal reference lines for better interpretability.

### Note

If 'type = "errorbar"', ensure that the 'std.error' column is present in the input dataframe. Missing values in the 'std.error' column for any term will result in incomplete confidence intervals.

### Examples

```
## Not run:
# Run event study
event_study <- run_es(
  data      = df,
  outcome   = y,
  treatment = is_treated,
  time      = year,
  timing    = 2005,
  lead_range = 5,          # Corresponds to years 2000-2004 (relative time: -5 to -1)
  lag_range  = 4,          # Corresponds to years 2006-2009 (relative time: 1 to 4)
  fe        = firm_id + year,
  cluster    = "state_id",
  baseline   = -1,
  interval   = 1
)

# Basic plot
plot_es(event_study)

# Use error bars instead of ribbon confidence intervals
```

```

plot_es(event_study, type = "errorbar")

# Adjust vertical reference line
plot_es(event_study, type = "errorbar", vline_val = -0.5)

# Customize axis breaks and title
library(ggplot2)
plot_es(event_study, type = "errorbar") +
  ggplot2::scale_x_continuous(breaks = seq(-5, 4, by = 1)) +
  ggplot2::ggtitle("Result of Event Study")

## End(Not run)

```

---

run\_es

---

*Run Event Study with Fixed Effects*


---

## Description

This function performs an event study using fixed effects regression based on a panel dataset. It generates dummy variables for each lead and lag period relative to the treatment timing, applies optional covariates and fixed effects, and estimates the model using `fixest::feols`.

## Usage

```

run_es(
  data,
  outcome,
  treatment,
  time,
  timing,
  lead_range,
  lag_range,
  covariates = NULL,
  fe,
  cluster = NULL,
  baseline = -1,
  interval = 1
)

```

## Arguments

data	A dataframe containing the panel dataset.
outcome	The outcome variable, specified unquoted. You may use a raw variable name (e.g., <code>'y'</code> ) or a transformation (e.g., <code>'log(y)'</code> ).
treatment	The binary treatment indicator (unquoted). Typically equals 1 in and after the treated period, 0 otherwise.

time	The time variable (unquoted). Used to calculate the relative timing.
timing	The time period when the treatment occurs for the treated units.
lead_range	Number of pre-treatment periods to include as leads (e.g., 5 = 'lead5', 'lead4', ..., 'lead1').
lag_range	Number of post-treatment periods to include as lags (e.g., 3 = 'lag0', 'lag1', 'lag2', 'lag3').
covariates	Optional covariates to include in the regression. Must be supplied as a one-sided formula (e.g., '~ x1 + x2').
fe	Fixed effects to control for unobserved heterogeneity. Must be a one-sided formula (e.g., '~ id + year').
cluster	Clustering specification for robust standard errors. Accepts either: <ul style="list-style-type: none"> <li>• a character vector of column names (e.g., 'c("id", "year")'), or</li> <li>• a one-sided formula (e.g., '~ id + year' or '~ id^year').</li> </ul> Cluster variables are internally re-evaluated after filtering for the estimation window.
baseline	The relative time (e.g., '-1') to use as the reference period. The corresponding dummy variable will be excluded from the regression and added manually to the results with estimate 0. Must lie within the specified 'lead_range' and 'lag_range'. If not, an error will be thrown.
interval	The interval between time periods (e.g., use '5' for 5-year spaced panel). Default is '1'.

## Details

This function is intended for difference-in-differences or event study designs with panel data. It automatically:

- computes relative time:  $(\text{time} - \text{timing}) / \text{interval}$ ,
- generates dummy variables for specified leads and lags,
- removes the baseline term from estimation and appends it back post-estimation,
- uses 'fixest::feols()' for fast and flexible estimation.

Both fixed effects and clustering are fully supported.

## Value

A tidy dataframe with the event study regression results, containing:

- 'term': Name of the lead or lag dummy variable.
- 'estimate': Coefficient estimate.
- 'std.error': Standard error.
- 'statistic': t-statistic.
- 'p.value': p-value.
- 'conf\_high': Upper bound of 95

- ‘conf\_low’: Lower bound of 95
- ‘relative\_time’: Time scaled relative to the treatment.
- ‘is\_baseline’: Logical indicator for the baseline term (equals ‘TRUE’ only for the excluded dummy).

## Examples

```
## Not run:
# Assume df is a panel dataset with variables: id, year, y, treat, x1, x2, var1, var2

# Specifying two-way clustering over var1 and var2 using a character vector:
run_es(
  data      = df,
  outcome   = y,
  treatment  = treat,
  time       = year,
  timing     = 2005,
  lead_range = 2,
  lag_range  = 2,
  covariates = ~ x1 + x2,
  fe         = ~ id + year,
  cluster    = c("var1", "var2"),
  interval   = 1
)

# Specifying two-way clustering over var1 and var2 using a one-sided formula:
run_es(
  data      = df,
  outcome   = y,
  treatment  = treat,
  time       = year,
  timing     = 2005,
  lead_range = 2,
  lag_range  = 2,
  covariates = ~ x1 + x2,
  fe         = ~ id + year,
  cluster    = ~ var1 + var2,
  interval   = 1
)

# Using an interaction in the clustering specification:
run_es(
  data      = df,
  outcome   = y,
  treatment  = treat,
  time       = year,
  timing     = 2005,
  lead_range = 2,
  lag_range  = 2,
  covariates = ~ x1 + x2,
  fe         = ~ id + year,
  cluster    = ~ var1^var2,
```

*run\_es*

7

```
    interval = 1  
)  
  
## End(Not run)
```

# Index

plot\_es, [2](#)

run\_es, [4](#)